


MATIONAL LEAD COMPANY



# LEAD




AS MANUFACTURED BY

National Lead Company

ATLANTIC BRANCH

111 BROADWAY NEW YORK



## lead Cames


THE cames shown in this booklet, representing one hundred and fifty different sizes, are made from a special grade of pig lead, assuring great durability, and are thoroughly milled in order to make the cement adhere and prevent leakage.

Particular attention is called to the reinforced cames on page 6. These cames are very desirable for use in country house work, where a flat surface is required for facility in cleaning. They can also be repaired very easily in case of breakage. This style of lead can be used in any kind of work where the use of bars for stay rods is not considered desirable. The steel strip running through the central groove of this lead will hold the work firmly in place.

Our came lead is packed in boxes of 100 pounds each, cut in lengths of six feet. Occasions frequently arise where a special lead for individual work is required which may call for the making of new dies. At such times, or at any other, we will be very glad to send our representative for consultation.

Our facilities being of the best, we can handle all business very quickly, making delivery in special cases in twenty-four hours.





A beautiful example of modern glazing art, illustrating the increased effectiveness derived from the use of the newly-produced "antique" lead cames described on the opposite page. These cames are made by a patented method by National Lead Company.

TT is now possible to obtain the exact effects found heretofore only in the old, expensive, hand-wrought cames. The soft, curving, irregular outline so much desired, as well as the hand-made surface effect, can be had in every length of Antique and Rustic Cames, with the further certainty that no two pieces will ever be exactly alike.

Four sizes are furnished reinforced. This consists of a steel bar embedded between the two hearts and milled in. making it water and airtight, and preventing any chance of corrosion of the steel bar.

> The plain is a single heart came without reinforcement.

5RR

5 A

E THER Antique or Rustic Cames may be had in the following sizes:


 $\frac{3}{4}'' \times \frac{3}{16}''$  Plain  $\frac{5}{8}$ " x  $\frac{3}{16}$ " Reinforced  $\frac{3}{4}$ " x  $\frac{3}{16}$ " Reinforced 5/8" x 3/8" Plain 5/8" x 3/8" Reinforced

 $\frac{1}{2}'' \times \frac{3}{16}''$  Plain  $\frac{1}{2}'' \times \frac{3}{16}''$  Reinforced


 $\frac{5}{8}$ " x  $\frac{3}{16}$ " Plain

 $\frac{3}{8}$ " x"  $\frac{3}{16}$  Plain


RUSTIC




## REINFORCED & CAMES




For use in all kinds of flat lead work where smooth surface is desirable, particularly for country house work, as all stay rods are eliminated.




## COLONIAL& HIGH HEART CAMES




These cames are particularly serviceable in colonial work and where double thickness of glass is required.




Very desirable in decorative house work where soft line and heavy effect are required.



For use in all commercial stained glasswork, being easier to work than flat leads.



Especially adaptable for all grades of figure work where heavy glass is required and for double and triple glazing.



These are cames we supply to those having their own milling machine to turn out unusual sizes for their own use.


## Weights of Cames

Per Six Foot Lengths

SIZE	WEIGHT	SIZE	WEIGHT	SIZE	WEIGHT
	RUSTIC A	ND ANTI	QUE CAME	S (Page 5)	)
3/4 "x3/16"P 30	1/2 groz.	5/8"x3/8"R	49 OZ.	1/2"x3/6"P	29 26 oz.
3/4 "x3/16"R 4	311 36	5/8"x3/16"P		1/2"x3/16"R	24 300
5/8"x3/8"P	5 32	5/8"x3/16"R	321/4	3/8"x3/16"P	11 16
0	PEN SLOT	REINFO	RCED CAM		
3/16 "	10½ OZ.	5/8"			I7 OZ
1/4"	. 13	3/4 "	25 1/2	5/8"R	221/4
3/8"	141/4	1/4 "x3/8"	121/4	1/2 "R	181/4
1/2 "	16½	3/8"x3/8"	203/4		
CL	OSED SLO	T REINF	ORCED CAI	MES (Pag	e 6)
58"	32 OZ.		39½ oz.	1/2 "	26 oz.
COL	ONIAL AN	D HIGH	HEART CA	MES (Pa	ge 7)
32	13 OZ.	103	173/4 OZ.	66	12 OZ.
33	1834	59	101/4	114	23 1/2
72	141/2	112	10	111	201/2
73	103/4	53	121/2	25	191/4
46	63/4	113	24 1/2	100	24
70	111/2	52C	10	31S	24
79	12	76	23 1/2	42	103/4
23	103/4	77	21 1/4		151/4
24	143/4	65	111/4	13	
3C	17 1/2	64	141/4	74	171/4
30	213/4	27	191/4	92	143/4
P	26		** *	45C	263/4
137	311/2	93	. 131/4 .	127 5 1	lbs. 103/4 02
1 3 /	31/2				
		LAT CAN	IES (Page 8)		
58	3 ½ OZ.	43	181/4 oz.	2	61/4 oz.
49	6	67	2 I	75	22
48	61/2	IO	93/4	62	151/4
83	7 1/2	5C1/2	1834	26	91/4
2C	73/4	35	13	55	121/2
3P	93/4	31	91/2	102	181/4
54	10	105	9	120	5 1/4
4C	131/2	104	91/2	128	27 1/2
14	151/2	56	I I 1/2	126	27
34	153/4	52	26	34S	151/4
1000000	173/4	86	5 1/2	4C-S	13
29	-//7				
52 <sup>1</sup> / <sub>2</sub>	34	43 1/2	21 1/2	3P-S	91/2

## Weights of Cames Per Six Foot Lengths

SIZE	WEIGHT	SIZE	WEIGHT	SIZE	WEIGHT
	R	OUND CA	MES (Page o	)	
1	43/4 OZ.	50	6½ oz.	3C1/2	143/4 OZ.
QI	61/2	6	13	4S	6
100	7 1/2	5 1	101/2	3	73/4
44	81/4	105	10	9	83/4
3S	7 1/2	8	131/4	4	10
106	81/2	1 1/2	123/4	1081/2	93/4
90	73/4	2 1	113/4	1 I	193/4
20	834	22	113/4	85	133/4
39	8	301C	121/2	7	121/4
6S	83/4	5	91/4	7S	11
*87	8	99	34 1/2	134	81/2
				135	63/4
98 98	GH HEAR	T FLAT	AND T CAM	IES (Page	25 02
97	101/2	88	11	1 T	10
9/	101/4	71	101/2	80	2.7
	11	84	203/4	110	4 lbs. 4 02
95	13	36	14 1/2	2 T	11
	103/4	41	17	3 T	8
63	141/4	119	53/4	5 T	12
40	113/4	78	161/4	7.2	
45	161/4	68	173/4		
	HEAVY C	AMES FO	R MILLING	G (Page 11	)
38	18½ oz.	57	48 oz.	18	40 OZ
17	2.4	19	35	115	22
C	36	116	18	107	25 1/4
15	213/4	125	101/2	108	163/4
60	25	69	28	101	53 1/2
94	41 1/4	82	26	16	32
28	313/4	81	221/2	61	56



#### Solder Either in the Form of Bar or Wire

Our wire solder is made by a process which insures absolute accuracy and uniformity of composition. Every mixing is tested and checked by three different people and a check sample retained for reference.

The alloy we recommend is that which melts at the lowest temperature and flows the freest, but we make up any composition upon request.

We use only the best brands of pig lead and pig tin. These metals fluctuate so greatly in price that it is impossible to name prices to hold good for any length of time, but our quotations are always as low as can be made upon a solder of good quality.

### Our Products

#### 111 PAINTERS' MATERIALS

White-Lead, Dry White-Lead-in-Oil Red-Lead, Dry Red-Lead-in-Oil Colors, Dry and in-Oil

Linseed Oil. American and Calcutta, Raw, Boiled, Refined, Varnishmakers'. Flatting Oil

#### BEARING METALS

Babbitt Metals

Ulco Metal Pressure Die Castings

#### PLUMBERS' MATERIALS

Lead Pipe , Block Tin Pipe Tin-lined Lead Pipe Lead Traps and Bends Solder

Soldering Flux

Leadamant Pipe

#### PRINTERS' METALS

Linotype Metal Monotype Metal Stereotype Metal Electrotype Metal

#### CANNERS' MATERIALS

Bar Solder Wire Solder Triangular Solder Ribbon Solder

Soldering Flux

#### LEAD OXIDES

Red-Lead Litharge Orange Mineral Glassmakers' Oxides Colormakers' Oxides

Rubbermakers' Oxides Varnishmakers' Oxides Enamelmakers' Oxides Potters' Oxides Accumulator Oxides

#### MISCELLANEOUS LEAD PRODUCTS

Sheet Lead Glaziers' Lead Bar Lead

Lead Wire Lead Sash Weights Piano Key Leads

#### GENERAL PRODUCTS

Brown Sugar of Lead White Sugar of Lead

Castor Oil Nitrite of Soda

Linseed Oil Cake and Meal Cinch Anchoring Devices

U. S. Cartridges and The Black Shells

